



Product Information Bulletin

F-Series Foamers Medium to Heavy Brine Drilling Foamer

DESCRIPTION:

F-Series Foamers have been formulated from anionic surfactants, builders, and foam boosters to provide excellent performance in medium to heavy brines of up to 10 Lbs. per gallon. F-Series Foamers are heavy duty foaming agents which were developed to be used in air mist / stable foam drilling applications, and which exhibits excellent tolerance to down hole influx of hydrocarbons, as well as high calcium tolerance.

Other applications for F-Series Foamers are as an aid in gas well unloading and cleanouts, where excellent results have been obtained at a more economical cost than soap sticks.

AVERAGE PHYSICAL PROPERTIES:

Density (Lbs./Gal)	8.545
Specific Gravity	1.0296
Flash Point	110°F
Pour Point	15°F
pH OF 5% Solution in water	8.0 – 9.0
Appearance	Light Amber Liquid
Ionic Charge	Anionic

Solubility

Fresh Water	Soluble
High TDS Brine Water	Soluble
Isopropanol	Soluble
Methanol	Soluble
Heavy Aromatic Solvent	Dispersible
Diesel Oil	Dispersible

USAGE:

During typical applications, F-Series Foamers are used at a concentration range of from 0.3 to 2.0 % by volume (2 to 8 gallons of F-Series Foamers per 10 Barrels of Brine water). These volumes are dependent on drilling methods, brine concentration, and down hole conditions.

F-Series Foamers may also be used to unload gas wells by either slugging 5 to 10 gallons down the production string via a wellhead lubricator, shutting the well in to allow the product to fall to the fluid level, and putting the well back on production, or by a continuous treatment down the annular space where possible, at a rate of from 1 quart to 2 gallons per day, based on the down hole conditions and the amount of fluids produced.

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY:

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.