



## Product Information Bulletin

### DF-100 Water Soluble Antifoam

---

#### **DESCRIPTION:**

DF-100 antifoam is a specially formulated liquid blend of antifoam agents for use in most applications. DF-100 can be used alone, or it can be used as a supplemental antifoam product to be applied in conjunction with other water treatment products where severe foaming problems are encountered.

#### **PHYSICAL PROPERTIES:**

Density (Lbs./Gal)	8.297
Specific Gravity (Water = 1)	0.996
Flash Point	N/A
Pour Point	N/A
Ionic Charge	Anionic

#### **Solubility**

Fresh Water	Soluble
High TDS brine	Soluble
Isopropanol	Soluble
Diesel Oil	Insoluble
Heavy Aromatic Solvent	Insoluble
Crude Oil	Insoluble

#### **USAGE:**

DF-100 antifoam can be applied directly to the system or into the suction or discharge side of the feed water pump. It should be applied on a continuous basis using a chemical proportioning pump. The proper federate will be determined by a Lone Star Industries representative.

## **HANDLING PRECAUTIONS:**

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

**DISCLAIMER OF LIABILITY** The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries' control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.