



Product Information Bulletin

FSC SERIES Foamer/Scale/Corrosion

DESCRIPTION:

FSC Series are Alkyl-Ether Sulfate foamer blended with a Scale/Corrosion/Inhibitor. FSC Series Foamer is used to foam produced fluids that may be restricting the flow of gas in marginal wells. The Scale Inhibitor in this product is High-Calcium Tolerant Scale Inhibitor used to inhibit calcium carbonate, calcium sulfate and barium sulfate scales. A Corrosion Inhibitor has been added to reduce the amount of iron loss due to C^{o2} or H^2S which might be found in produced gases.

AVERAGE PHYSICAL PROPERTIES:

Density (Lbs per Gal)	8.2
Specific Gravity (Water = 1)	1.0
Flash Point	141°F
Pour Point	N/A
PH	7
Ionic Charge	

SOLUBILITY:

Solubility	
Fresh H ² O	Soluble
High TDS Brine	Soluble
Oil	Insoluble

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries' control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.