



Product Information Bulletin

Foamer/Corrosion Inhibitor

DESCRIPTION:

Foamer/Corrosion Inhibitor is an Alkyl-Ether Sulfate foamer blended with a Corrosion Inhibitor. Foamer/Corrosion Inhibitor is used to foam produced fluids that may be restricting the flow of gas in marginal wells. A Corrosion Inhibitor has been added to reduce the amount of iron loss due to CO² or H²S which might be found in produced gases.

PHYSICAL PROPERTIES:

Density (Lbs per Gal)	8.2
Specific Gravity (Water = 1)	1.0
Flash Point	141°F
Pour Point	N/A
PH	7
Ionic Charge	

SOLUBILITY:

Solubility	
Fresh H ² O	Soluble
High TDS Brine	Soluble
Oil	Insoluble

Foamer/Corrosion Inhibitor

HANDLING PRECAUTIONS:

For information regarding safety precautions in handling, health hazards, and exposure, please refer to the material safety data sheet for this product. In case of emergency, please call (361) 527-4460.

DISCLAIMER OF LIABILITY

The information in this bulletin is believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Lone Star Industries' control. The listed properties are illustrative only, and not product specifications. Lone Star Industries disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other material or in any process.