



Product Information Bulletin

AS-526 A WEIGHTED SOLID PERFORMANCE PRODUCT

DESCRIPTION:

AS-526 is a weighted solid performance product that is composed entirely of water soluble components produced in a cylindrical form. This product is designed to remove inorganic and hydrocarbon solids which cause a loss of production efficiency. **AS-526** may be used to remove deposits in gas wells, oil wells, and injection wells.

USAGE:

In order to remove solids from any type of well the weighted **AS-526** units are dropped down the tubing. Because **AS-526** is a weighted product it will rapidly fall to the bottom of the well into the water layer. The number of the product units needed will vary with the amount of deposits present. After a particular well is cleaned up a regular treating program is recommended. Your **Lone Star Industries Representative** will work with you on designing an effective treating program.

TYPICAL PHYSICAL PROPERTIES:

Form	Solid, Cylindrical
Color	White
Density @ 77°F (g/ml)	1.313
Density @ 77°F (lb/gal)	11.19
pH 2 % solution	2.7

HANDLING AND STORAGE:

AS-526 is an industrial chemical. All safety and handling warnings on the product container and the material safety data sheet should be observed for detailed disposal information please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

AS-526 is available in a 5 gallon container and 55 gallon split top drums from **Lone Star Industries**, P.O. Box 188, Hebbbronville, Texas 78361

Please Call: (361) 527-4460

Fax: (361) 527-3089