



Product Information Bulletin

LSS-537

DESCRIPTION:

LSS-537 is a color coded water soluble performance product that has been designed to unload produced fluids from gas wells.

LSS-537 is a synergistic blend of several water soluble components that work together to form a with a high water content.

LSS-537 has a moderate tolerance for liquid hydrocarbons and has low emulsions forming tendencies.

USAGE:

LSS-537 is especially effective for unloading wells that produce from 5 to 10 barrels of water per day. Most often 2 to 6 units are all that are needed to unload the well. Your **Lone Star Industries Representative** will work with you on designing an effective treating program.

TYPICAL PHYSICAL PROPERTIES:

Form	Solid, Cylindrical
Color	Blue
Density @ 77°F (g/ml)	1.208
Density @ 77°F (lb/gal)	10.66
pH of 1% solution	7.14

HANDLING AND STORAGE:

LSS-537 is an industrial chemical product. All safety and handling warnings on the product container and the material safety data sheets should be observed. For detailed safety and disposal information please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

LSS-537 is available in 5 gallon containers and split top 55 gallon drums from **Lone Star Industries**, P.O. Box 188, Hebronville, Texas 78361.

Please Call: (361) 527-4460

Fax: (361) 527-3089